



LIFTING FOR SAFETY :



PREFERRED METHOD

BASE = LENGTH(L, Length of Leg)



MAXIMUM RECOMMENDED*

0.5 X BASE = HEIGHT(H)

Do not use slings at angles greater than 120° as the horizontal forces place too much load on the sling legs
 *Maximum 60° angle for reeved and basket slings

LOAD CAPACITIES :

ALLOY GRADE (T80) CHAIN SLINGS To AS 3775.1-2014

CHAIN DIA. mm	SINGLE LEG SLINGS			SLINGS OF 2,3 OR 4 LEGS			ENDLESS SLINGS		Reeved sling
	Straight lift	Straighted straight lift	Reeved sling	60°	90°	60° (max)	60°	90°	
6	11	1.1	0.8	1.9	1.6	1.5	1.5	1.2	1.7
7	1.5	1.5	1.1	2.6	2.1	2.0	2.0	1.6	2.3
8	2.0	2.0	1.5	3.5	2.8	2.6	2.6	2.1	3.0
10	3.2	3.2	2.4	5.5	4.5	4.1	4.1	3.4	4.8
13	5.3	5.3	4.0	9.2	7.5	6.9	13	13	8.0
16	8.0	8.0	6.0	13.8	11.3	10.4	14.5	11.9	5.6
19	11.2	11.2	8.4	19.2	15.8	14.5	14.5	11.9	5.6
20	12.5	12.5	9.4	21.6	17.6	16.3	16.3	13.3	18.8
22	15.0	15.0	11.3	26.0	21.2	19.5	19.5	15.9	22.5
26	21.2	21.2	15.9	36.7	29.9	27.6	27.6	22.5	31.8
32	31.5	31.5	23.6	54.5	44.4	41.0	41.0	33.4	47.3

NOTE: The quoted W.L.L is approximate and relevant to Grange Lift products.